# **Technical Specifications**

### **HP E24i G4 WUXGA Monitor**




1. OSD Buttons

**Front** 

2. Power Button

# **Technical Specifications**

### **HP E24i G4 WUXGA Monitor**



- 1. Power Connector
- 2. DisplayPort™
- 3. HDMI Port
- 4. VGA Port

### Back

- 5. USB-B Port
- 6. USB-A Ports (2)
- 7. USB-A Ports (2)

#### **Technical Specifications**

Models: 9VJ40AA

**Panel Specifications Display Size (Diagonal)** 24-in **Display Panel Type IPS** 

> Micro-Edge Bezel Yes, 3-sided **Native Resolution/Timing** 1920 x 1200 @60Hz Panel Bit Depth 8bit (6bit + FRC)

**Aspect Ratio** 16:10 **Brightness - Typical** 250 cd/m<sup>2</sup> Static Contrast Ratio - Typical 1000:1 **Static Contrast Ratio - Minimum** 700:1 **Dynamic Contrast Ratio (DCR)** 5M:1 Flicker Free Yes

**Pixel Pitch** 0.2745 (H) × 0.2745(V)

Pixels Per Inch (PPI)

Backlight Lamp Life (to half brightness 30k minimum

- in hours)

**Anti-Glare Panel** Yes

**Response Time - Typical** 5ms GtG (with overdrive)

**Horizontal Viewing Angle (typical** 178°

Vertical Viewing Angle (typical CR>10) 178°

Panel Active Area (w x h) 527.04(H) × 296.46(V) mm

**Preset Graphic Modes/Supported** 640 × 480 @60Hz Resolutions 720 × 400 @70Hz

800 × 600 @60Hz 1024 × 768 @60Hz 1280 × 720 @60Hz 1280 x 800 @60 HZ 1280 × 1024@60Hz 1440 × 900 @60Hz 1600 × 900 @60Hz 1680 × 1050 @60Hz

**Maximum Resolution** 1920 × 1200 @60Hz **Recommended Resolution** 1920 × 1200 @60Hz

Vertical Scan Range 50-60Hz **Horizontal Scan Range** 30-80kHz **Default Color Temperature** Neutral (6500K)

NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

**Color Gamut Coverage** NTSC 72%

RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2 **Color Management** Color Space / Subsampling Support

> **Default Color Temperature** Neutral (6500 K)

**Low Blue Light Modes** Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution

certified)

**RGB Channel Adjust** Yes

**Monitor Specifications Exterior Color of Monitor Bezel and** Black head, Silver stand

Stand

Plug & Play Yes

Tilt -5° to +23°

#### **Technical Specifications**

+/-45° **Swivel** Pivot +/-90° **Height Adjustment Range** 150mm Yes. 100 mm **VESA Mounting** 

**Security Lock Ready** Yes

**Detachable Base** Yes, ships detached Based on region Warranty

**On Screen Display** 

(OSD)

**On Screen Display User Controls** Brightness+, Color, Image, Input, Power, Menu,

Management, Information

Menu, Minus ("-")/Information, Plus ("+") / Viewing Mode, **Monitor Control Buttons or Switches** 

OK/Next Active Input, Power

Yes, 3 (6 Options) **User-Assignable Function Buttons** 

10 (German, Dutch, T-Chinese and S-Chinese, English, Languages

Spanish, French, Italian, Japanese, Portuguese)

**Connector Types** 

DisplayPort™ HDMI

1 DisplayPort™ 1.2 in

1 HDMI1.4

**VGA** 

**HDCP** support Yes, (DisplayPort™ and HDMI)

**USB Port Specifications**  **USB Version** 

3.2

Yes

16 W

24 kWh

1

**USB Hub** Yes **Downstream Ports** 4 Ports **Upstream Ports** 1 Port

**Fast Charging USB Ports** 1 Port (Side) (USB-A) **Power Output Maximum** Fast Charging: 7.5 W

**Special Features** 

**User Presets User Updateable Firmware** 

**Power & Operating** 

Specs

Yes **Power Supply** Internal

**Power Source** 100 - 240 VAC 50/60 Hz

**Power Consumption - Maximum** 35 W **Energy Saving/Standby Mode** 0.5 W **Power Consumption - Typical** 36 W Power cable length 1.9 m

**EU Energy Efficiency** Class (EC1062)

**On-mode Power Consumption** 

(EC 1062/2010) **Annual Power Consumption** 

(EC 1062/2010)

Energy Efficiency Class (EC 1062/2010)

Visible Screen Size 24" / 60.69 cm Diagonal

**Operating Conditions** 

**Operating Temperature - Celsius** 5°-35°C **Operating Temperature - Fahrenheit** 41°C - 95°F Non-operating Temperature - Celsius  $-34^{\circ} - 60^{\circ}C$ Non-operating Temperature --29° - 140°F

**Fahrenheit** 

**Operating Humidity** 20 – 80% Relative Humidity (non-condensing)

**Non-operating Humidity** 5 - 95%

**Operating Altitude** 0 – 5.000 m (16.400 ft.) **Non-operating Altitude** 0 – 12,192 m (40,000 ft.)

#### **Technical Specifications**

<b>Environmental</b>
Features and
Certifications

Mercury-free LED display backlighting

Arsenic-Free Display Glass

Low Halogen\*

Yes, Mercury-free LED backlighting

Yes Yes

GSE HP-00011-01B, table 2 defines low-halogen (BFR, CFR,

NOTE: External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained

after purchase may not be Low Halogen.

**Agency Approvals and Certifications** 

CE. CB. KC/KCC/NOM/ISO 9241-307/ EAC/TUV-GS/cTUVus/PSB/CCC/CEL/ISC/VCCI/FCC/BSMI/Vietnam

**Microsoft WHQL Certification** 

**ENERGY STAR®** 

**EPEAT® Registered\* TCO Certified** 

**China Energy Label** SmartWay Transport Partnership - NA

only

MEPS/Australian-New Zealand MEPS/WEEE/BIS/CEC/E-Standby/Low Blue Light/CECP/TUV-S/CECP

Win 10, Win 8, Win 7 Yes, ENERGY STAR® 8

CEL Grade 1 Yes (NA SKU)

Yes

Yes

WW certificate

\*External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

NOTE: DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

#### **Contains Recycled Plastics**

Container Load. 20-Foot

85% recycled content by total weight

<b>Unit Product/Package</b>
Specifications

**Pallet Information** 

	<u>Metric</u>	<u>Imperial</u>
Product Dimensions (Unpacked with stand) (W x D x H)	53.2 x 20.69 x 50.96 cm	20.94 x 8.15 x 20.06 in
Product Dimensions (Packed) (W x D x H)	60.5 x 42 x 22.4 cm	23.82 x 16.54 x 8.82 in
<b>Display Head Dimensions</b> (Unpacked without stand) (W x D x H)	53.2 x 4.7 x 35.27 cm	20.94 x 1.85 x 13.88 in
Base Area Footprint (w x d mm)	260 x 207 mm	10.23 x 8.15 in
Bezel Measurements	Bottom 20.73 mm (display chin)	Bottom 8.16 in (display chin)
Product Weight (Unpacked with stand)	6.06 kg	13.36 lb
Product Weight (Packed)	9.12 kg	20.1 lb
Product Weight (Head Only)	3.6 kg	7.94 lb
Pallet Dimensions (L x W x H)	1220 x 1140 x2243 mm	48.03 x 44.88 x 88.31in
Pallet Total Weight (L x W x H)	40" GQ: 384 kg 40" HQ: 476 kg	40" GQ: 847 lbs 40" HQ: 1050 lbs
Pallet Layers	GQ: 4 HQ: 5	
Pallet Product per Layer	8	
Total Products per Pallet	GQ: 32	

HQ: 40

460

#### **Technical Specifications**

**Container Load, 40-Foot** 960 **Container Load, 40-Foot HighQ** 960

**Software Included** HP Display Center

**What's in the box?** 1 HDMI (1.8 m) 5.9 ft

1 DisplayPort™ (DisplayPort™ 1.2) (1.8 m) 5.9 ft 1 USB-A-B cable (1.8 m) 5.9 ft 1 Power Cord (1.9 m) 6.2 ft

1 QSP 1 Doc-Kit

User Guide and Warranty Languages **User Guide Languages** English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.

**Warranty Languages** English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.



### **Technical Specifications**

Copyright © 2021 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



# Summary

Change Log				
January 3, 2021	V1 to V2		Techspecs updated	

