

NIPPON KAIJI KYOKAI



TYPE APPROVAL CERTIFICATE FOR AUTOMATIC DEVICES AND EQUIPMENT

Certificate No.TA21097M

This is to certify that the undernoted product(s) has/have been approved in accordance with the requirements specified in Chapter 1, Part 7 of "Guidance for the Approval and Type Approval of Materials and Equipment for Marine Use" and the relevant Society's Rules.

This certificate is issued to

Manufacturer:

Mariner Systems (UK) Ltd.

Place of Manufacturing:

Oaklands Park, Wokingham, Berkshire, RG41, 2FD, UK

Product description:

Mariner Kit for Personal Computer

Model:

Mariner Kit MS2550, MS2560, MS2570 and MS2580 for HP

EliteDesk 800 G5 Small Form Factor (SFF) and Tower (TWR)

PC

Approval No.:

21A004

Valid until:

2 March 2026

This certificate is subject to the conditions specified in the attached sheet(s).

Issued at Tokyo on 3 March 2021.

T. Shimada
General Manager
Machinery Department

NIPPON KAIJI KYOKAI

Attached sheet -1/2 to the Certificate No. TA21097M

Specification & documents:

1. Particulars:

Power supply: AC $100V \sim 240V$, 50 / 60Hz

2. Components and reference drawings:

Component	Drawing	
HP EliteDesk 800 G5 Small Form Factor (SFF)	HP EliteDesk 800 G5 QuickSpec v.15	
HP EliteDesk 800 G5 Tower (TWR) PCs		
Mariner Kit (Used with above)	MS2550_A, MS2560_A,	
• MS2550, MS2560, MS2570, MS2580	MS2570_A, MS2580_A	

3. Documentation and Test Reports:

- Test Report TL19106 (Issue 1: 5th December 2019, Issue 2: 30th March 2020)
- Test Report TL19111 (Issue 1: 5th December 2019, Issue 2: 30th March 2020)
- Test Report TL19112 (Issue 1:5th December 2019, Issue 2: 30th March 2020)
- Flame Retardant Test Report R21-5423 for Mariner Kit (3rd March 2021)
- Marine Type Approval Test Requirements Issue 4th October 2019 (Including flame retardant Material declaration)

- To be continued -

NIPPON KAIJI KYOKAI

Attached sheet -2/2 to the Certificate No. TA21097M

Test items & approval conditions:

1. Test items:

(Applied testing items are marked with X.)

ENVIRONMENTAL TESTS (IACS UR E10 Rev.7 basis)		Mark	
External examination		X	
Operation test and performance test		X	
Electric power supply failure test		X	
Power supply fluctuation test		Electric	X
		Pneumatic and Hydraulic	
Insulation resistance test		X	
High voltage test		X	
Pressure test (Pneum	(Pneumatic and Hydraulic)		
Dry heat test (Tempe	t (Temperature 70° C × 16 hours)		X
Damp heat test		X	
Vibration test (Acceleration $\pm 1.0 \text{g} \times 2 \text{ hours}$)		X	
Inclination test		X	
Cold test (Temperature $-25^{\circ}C \times 16$ hours)		X	
Salt mist test			
Electrostatic discharge immunity test		X	
Radiated radio frequency immunity test		X	
Conducted low frequency immunity test		X	
Conducted high frequency immunity test		X	
Burst / Fast transient immunity test		X	
Surge immunity test			X
Radiated emission test			X
Conducted emission test			X
Flame retardant test			X

2. Approval condition:

The product is not allowed to be installed on open decks.